YASKAWA

MOTOMAN SG400

Picking, Packing & Handling with the SG-series

The robust MOTOMAN SG400 scara-robot features a wide motion range due to its compact design.

It is particularly suitable for application when high speed and accuracy is required, for example picking and packing, dispensing and feeding. Small interference contours allow the robots working together in confined spaces. Internal cabling enables a reliable workflow and saves extensive maintenance

The SG400 is driven by the compact and lightweight YRC-1000micro controller.




KEY BENEFITS


- Fast, powerful and reliable
- Wide motion range
- Compact and robust design
- Internal cabling
- High repeatability and accuracy
- Ideal for applications in confined spaces
- Easy integration and high dynamics
- Easy maintenance




MOTOMAN SG400









View A



View B



View C



View E

Mounting option: Floor


Maximum payload of the wrist axis and the R-axis allowable inertia


Please make sure that the load (total amount of hand and workpiece) does not exceed the values in the table.

Max. Payload [kg]	3
R-axis allowable inertia [kg · m²]	0.06
Max. allowable eccentric distance of the mass center point [mm]	150

View D

Media connector





Specifications SG400							
Axes	Maximum motion range [°]	Maximum speed [°/sec.]	Allowable moment [Nm]	Allowable moment of inertia [kg · m²]	Controlled axes	4	
					Max. payload [kg]	3	
s	±142	740	-	-	Repeatability [mm]	±0.01	
L	±147	800	-	-	Max. working range R [mm]	400	
U	+200	1200 mm/sec.	-	-	Temperature [°C]	0 to +40	
R	±360	3000	-	0.06	Humidity [%]	20 – 80	
					Weight [kg]	14	
					Power supply, average [KVA]	1	

Yaskawa Europe GmbH

Robotics Division Yaskawastraße 1 85391 Allershausen Germany Tel. +49 (0) 8166 90-0 robotics@yaskawa.eu.com www.yaskawa.eu.com YR-1-04SX400-A00 A-03-2020, A-No. 210156

